



GC2929W, Mechanical Grounding Connector, Two Cables to Bar, Tin Plated

By Burndy
Catalog # [GC2929W](#)



Mechanical Grounding Connector, 2 Cables to 1/4" Thick Bar, 2/0 AWG (Sol) -250 kcmil, 1/2" Stud, Torque: 480 lb in, Hot Tin Dipped

Specifications

Certification - cULus	No
Certification - UL Recognized	No
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Industry Standard(s)	UL467
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes
Buy America(n) Qualified	Contact Manufacturer

Conductor

Conductor - Copper Solid Size	2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Size Range	2/0 AWG - 250 KCMIL
Conductor - Copper Str Size	2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Str Size Range	2/0 AWG - 250 kcmil

Dimensions

Dimension - Width inch	2.04 in
Dimension - Width mm	52 mm
Dimension - L Length Overall mm	32 mm

Dimension - Height inch	2.32 in
Dimension - Height mm	58.9 mm
Dimension - Length Overall inch	1.25 in
Dimension - Width fraction	2 in

Force Related

Installation Torque Recommended in-lb	480 lb-in
---------------------------------------	-----------

General

Physical Attribute - Screw Type Plated	Hexagonal Bolt Y
Material Type - Screw	DURIUM™ Silicon Bronze
UPC 12 Digit	781810054246
UPC 14 Digit GTIN	00781810054246
Material	Copper
Plating Type	Tin - Hot Dipped
UPC	781810054246

Logistics

Minimum Pack Quantity	1
Carton Quantity	12
Pallet Quantity	2400

Product Assets

[Catalog \[English\]](#)